Radiator Brace Installation

1 Remove seat, gas tank, radiator shrouds, and plastic louvers

2 Drain radiator coolant, by removing the radiator cap and then the coolant drain plug on the side of the water pump (Fig 1)

3 Reinstall coolant drain plug.

4 Loosen the hose clamps on the top of the radiators, then pull the hoses off the radiators (Fig 2)

5 Remove the 4 bolts holding the radiators to the frame

6 Place the brace marked with an R on the back of the right radiator (Fig 3)

7 Using two of the supplied 6x8mm button head bolts install the smaller half of the brace on the outside edge of the radiator (Fig 4)

8 Install the top and bottom support rods using 4 of the supplied 6x16mm button head bolts (Fig 5)

9 Place the brace marked with an L on the back of the left radiator

10 Repeat steps 6 and 7

11 Reconnect the radiators with the braces installed on the back side, using the supplied 6x30mm hex head bolts, stock washers, and supplied washers (Fig 6&7)

12 Fill radiators with coolant

13 Install tank & seat

14 Fasten the radiator shrouds to the radiators using the supplied 6x25mm hex head bolt with the stock washers and supplied spacer (Fig 8&9)




FIG 1


FIG 2


FIG 3



FIG 4


FIG 5


FIG 6



FIG 7


FIG 8


FIG 9

WARNING AND DISCLAIMER

All parts manufactured, designed or sold by Moose Racing ("Moose") should be installed by a qualified motorcycle technician. Riding motorcycles can be dangerous. Serious injury, death and property damage can occur. Injury is increased by improper installation or misuse of equipment. Moose's customers must exercise good judgment in the use, control, alteration, part selection and installation, and maintenance of their motorcycles. In the event of a possible defect in material or design, or any other defect in a part manufactured, designed or sold by Moose, the responsibility of Moose is limited to a refund of the purchase price or the replacement of the part if Moose determines the part to be defective, and subject to Moose's inspection of the part within thirty (30) days from the date of purchase. (Note: any attempted repairs or modifications made to Moose products will void this limited warranty). Moose, under no circumstances will be responsible for incidental and/or consequential damages, property damage, personal injury damage, or damage, injury, cost or expense of any kind or nature whatsoever except as provided by law. Moose makes no other warranty, express or implied, including without limitation any warranties of merchantability and fitness for a particular purpose.

MOOSERACING®

INSTRUCTIONS

RADIATOR BRACE INSTALLATION

Part#'S *#1901-0141(04-08 cr250), 1901-0142(04-09 crf 250), 1901-0143(04-09 crf 250x), 1901-0144(04-08 crf 450), 1901-0145(04-09 crf 450x)*

For questions please contact:
customerservice@enduroeng.com